




perma FUTURA

For high corrosion, high humidity and high contamination environments



Activator -Discharge period in months

PART #	DESCRIPTION	1 MONTH	3 MONTHS	6 MONTHS	12 MONTHS
SF01FUTURA	FUTURA 120CC PERMA MULTI-PURPOSE GREASE	Activator -1	Activator -3	Activator -6	Activator -12
SF10FUTURA	FUTURA 120CC PERMA FOOD GRADE GREASE				

perma FUTURA Installation Kits available on request.

The **Perma FUTURA 120** is a robust, single-point automatic lubrication system designed for reliable performance in harsh and corrosion-prone environments. With a transparent plastic housing and electrochemical drive, it delivers consistent lubrication without the need for external power.

Using a simple activator screw, the unit dispenses **120 cc of lubricant** over selectable periods of **1, 3, 6, or 12 months**, ensuring continuous lubrication to bearings, chains, and mechanical components.

Key Features:

- Electrochemical drive (no batteries or external power required)
- Transparent, corrosion-proof housing for visual monitoring
- Adjustable discharge periods (1–12 months)
- Delivers up to 120 cm³ of grease or oil (NLGI 2 compatible)
- Pressure build-up up to 4 bar for consistent lubricant delivery
- Suitable for hazardous and mining environments (Ex-certified)

Applications:

Ideal for **roller bearings, sliding bearings, chains, open gears, and seals**, particularly in industries where hygiene, moisture, or corrosion are concerns—such as mining, food processing, and heavy industry.

“Fluid Equipment Specialists”

SALES@SILVERIENG.COM | 1300 766 413 | WWW.SILVERIENG.COM