



DIESEL NOZZLE SWIVELS

Fast Fill Swivels are widely used on fuel nozzles, hose reels, service trucks, lubrication systems, and high-flow diesel transfer systems where reliability, contamination control, and operational efficiency are critical.

- Reduces hose kinking and twisting
- Improves operator ergonomics and handling
- Extends hose and coupling service life
- Smooth 360° rotational movement
- Heavy-duty construction for harsh environments
- Available in aluminium and steel configurations
- Ball bearing designs for high-flow applications
- Suitable for mining, transport, industrial, and mobile equipment



MINING | QUARRY | CONSTRUCTION

"Fluid Equipment Specialists"

SALES@SILVERIENG.COM | 1300 766 413 | WWW.SILVERIENG.COM

DIESEL NOZZLE SWIVELS

Fast Fill Swivels are engineered to provide smooth hose movement, reduced hose stress, and improved operator handling during fuel and fluid transfer operations in demanding industrial environments. Designed for mining, construction, transport, oil & gas, and heavy equipment applications, Fast Fill swivels improve hose flexibility while minimising hose twisting, premature wear, and operator fatigue.

Manufactured from high-quality aluminium, steel, and precision-machined components, Fast Fill Swivels are built to withstand harsh operating conditions while maintaining reliable performance under continuous use. Selected models incorporate heavy-duty ball bearing designs, allowing smooth rotational movement under high flow and high-pressure conditions.

Available in a wide range of thread configurations and sizes, including NPT and BSPT options, Fast Fill Swivels are suitable for fuel, oil, lubrication, and fluid transfer systems. The range includes standard swivels, steel swivels, multiplane swivels, rebuild swivels, and high-flow heavy-duty configurations for large-scale refuelling applications.



PART NUMBER	IMPERIAL & METRIC INFORMATION
S75	3/4 IN. NPT MALE X 3/4 IN. NPT FEMALE (19 mm NPT MALE X 19 mm NPT FEMALE)
AWS34	3/4" SWIVEL (19 mm SWIVEL)
S100	1" SWIVEL (25 mm SWIVEL)
AC1010	ANODISED BASE MULTIPLANE SWIVEL, 1 IN. NPT MALE X 1 IN. NPT FEMALE(25 mm NPT MALE X 25 mm NPT FEMALE)
S125	HOSE SWIVEL 1 1/4" (32 mm)
S150	HOSE SWIVEL 1 1/2" STYLE BALL BEARING (38 mm)
S150-BSPT	HOSE SWIVEL 1 1/2" BSPT (38 mm BSPT)
S150 (MC)	SWIVEL 1 1/2" X 1 1/2" (38 mm X 38 mm)
S150R	1 3/4" NOZZLE REBUILD SWIVEL "B" STYLE BALL BEARING (44 mm)
S150S	STEEL HOSE SWIVEL 1 1/2" (38 mm)
S1510	HOSE SWIVEL 1 1/2" (38 mm)
S200	HOSE SWIVEL 2" "B" STYLE BALL BEARING (50 mm)
S200 (MC)	HOSE SWIVEL 2" (50 mm)
S215	HOSE SWIVEL WITH 2" NPT MALE THREADS AND 1.5" FEMALE THREADS "B" STYLE BALL BEARING (50mm x 38mm)
S215S	STEEL HOSE SWIVEL WITH 2" NPT MALE THREADS AND 1.5" FEMALE THREADS (50mm x 38mm)
S512	HOSE SWIVEL 1 1/2" MALE NPT X 2" FEMALE NPT (38 mm MALE NPT X 50 mm FEMALE NPT)

"Fluid Equipment Specialists"

SALES@SILVERIENG.COM | 1300 766 413 | WWW.SILVERIENG.COM