



STANDARD FLUID COUPLERS


CRANKCASE

COOLANT

HYDRAULIC

TRANSMISSION

MINING | QUARRY | CONSTRUCTION



Only Trust your "FLUID EQUIPMENT SPECIALISTS"

WWW.SILVERIENG.COM | SALES@SILVERIENG.COM | 1300 716 413 | WHATSAPP +61 458 047 075

STANDARD FLUID COUPLERS **CRANKCASE**

Designed for transferring the primary fluids used on heavy equipment. Nozzle and receiver pairs only connect with their corresponding size and colour.

R100C

CRANKCASE RECEIVER & CAP



R100JC *

CRANKCASE RECEIVER & CAP



R100RC #

"R SERIES" CRANKCASE
RECEIVER & CAP



N100P- PL

CRANKCASE NOZZLE & PLUG PIN
LATCHING



N100P

CRANKCASE NOZZLE WITH PLUG, BALL
LATCH, 3/4"



N100RP #

"R SERIES" CRANKCASE NOZZLE
WITH PLUG, BALL LATCH, 3/4"



STANDARD

OPERATING PRESSURE	BURST PRESSURE	FLOW AREA	NOZZLE THREAD	RECEIVER THREAD
34.5 BAR	103.4 BAR	.305 SQ "	3/4" MNPT	3/4" MNPT
500 PSI	1500 PSI	7.74954 mm	19.05 mm	19.05 mm

R SERIES

OPERATING PRESSURE	BURST PRESSURE	FLOW AREA	NOZZLE THREAD	RECEIVER THREAD
34.5 BAR	103.4 BAR	.364 SQ "	3/4" FNPT	OD 1-5/8" 12 TPI ID 1-5/16"
500 PSI	1500 PSI	9.2456 mm	19.05 mm	41mm OD, 34 mm ID

*JIC bases on these receivers have extended JIC threads that can be fitted into a bulkhead; a female JIC hose can then be attached on the other side of the bulkhead. # R Series used for remote bulkhead mounting for common fluids. The receiver's dual threads are designed to allow bulk-head mounting using the male thread and connection of a hose to a leak-free female ORB thread. Note: R series couplers DO NOT connect with Standard couplers.

Only Trust your "FLUID EQUIPMENT SPECIALISTS"

WWW.SILVERIENG.COM | SALES@SILVERIENG.COM | 1300 716 413 | WHATSAPP +61 458 047 075

STANDARD FLUID COUPLERS COOLANT

Designed for transferring the primary fluids used on heavy equipment. Nozzle and receiver pairs only connect with their corresponding size and colour.

R200C
COOLANT RECEIVER & CAP



R200JC *
COOLANT RECEIVER & CAP



R200RC #
"R SERIES" COOLANT RECEIVER & CAP




N200P
COOLANT NOZZLE & PLUG PIN LATCHING



N200UP
COOLANT NOZZLE WITH PLUG, BALL LATCH, 3/4"



N200RP #
"R SERIES" COOLANT NOZZLE WITH PLUG, BALL LATCH, 3/4



STANDARD

OPERATING PRESSURE	BURST PRESSURE	FLOW AREA	NOZZLE THREAD	RECEIVER THREAD
34.5 BAR	103.4 BAR	.112 SQ "	1/2" MNPT	1/2" MNPT
500 PSI	1500 PSI	2.8448 mm	12.7 mm	12.7 mm

R SERIES

OPERATING PRESSURE	BURST PRESSURE	FLOW AREA	NOZZLE THREAD	RECEIVER THREAD
34.5 BAR	103.4 BAR	.136 SQ "	1/2" FNPT	OD 1-3/16" 12 TPI ID 7/8" 14
500 PSI	1500 PSI	3.4544 mm	12.7 mm	TPI (-10 ORB) 30.16 mm OD, 22.25 mm ID

*JIC bases on these receivers have extended JIC threads that can be fitted into a bulkhead; a female JIC hose can then be attached on the other side of the bulkhead. # R Series used for remote bulkhead mounting for common fluids. The receiver's dual threads are designed to allow bulk-head mounting using the male thread and connec-

Only Trust your "FLUID EQUIPMENT SPECIALISTS"

WWW.SILVERIENG.COM | SALES@SILVERIENG.COM | 1300 716 413 | WHATSAPP +61 458 047 075

STANDARD FLUID COUPLERS **HYDRAULIC**

Designed for transferring the primary fluids used on heavy equipment. Nozzle and receiver pairs only connect with their corresponding size and colour.

R300C
HYDRAULIC RECEIVER & CAP



R300JC *
HYDRAULIC RECEIVER & CAP



R300RC #
"R SERIES" HYDRAULIC RECEIVER & CAP



N300P
HYDRAULIC NOZZLE & PLUG PIN LATCHING



N300BP
HYDRAULIC NOZZLE WITH PLUG, BALL LATCH, 3/4"



N300RP #
"R SERIES" HYDRAULIC NOZZLE WITH PLUG, BALL LATCH, 3/4"



STANDARD

OPERATING PRESSURE	BURST PRESSURE	FLOW AREA	NOZZLE THREAD	RECEIVER THREAD
34.5 BAR	103.4 BAR	.2212 SQ “ 5.61848 mm	3/4” MNPT	3/4” MNPT
500 PSI	1500 PSI	[N300BP	19.05 mm	19.05 mm

R SERIES

OPERATING PRESSURE	BURST PRESSURE	FLOW AREA	NOZZLE THREAD	RECEIVER THREAD
34.5 BAR	103.4 BAR	.421 SQ “	1” FNPT	OD 1-7/8” 12 TPI ID 1-5/8” 12 TPI
500 PSI	1500 PSI	10.6934 mm	25.4 mm	47.625 mm OD, 41.275 mm ID

*JIC bases on these receivers have extended JIC threads that can be fitted into a bulkhead; a female JIC hose can then be attached on the other side of the bulkhead. # R Series used for remote bulkhead mounting for common fluids. The receiver’s dual threads are designed to allow bulk-head mounting using the male thread and connection of a hose to a leak-free female ORB thread. Note: R series couplers DO NOT connect with Standard couplers.

Only Trust your “FLUID EQUIPMENT SPECIALISTS”

WWW.SILVERIENG.COM | SALES@SILVERIENG.COM | 1300 716 413 | WHATSAPP +61 458 047 075

STANDARD FLUID COUPLERS TRANSMISSION

Designed for transferring the primary fluids used on heavy equipment. Nozzle and receiver pairs only connect with their corresponding size and colour.

R400C

TRANSMISSION RECEIVER & CAP



R400JC *

TRANSMISSION RECEIVER & CAP



R400RC

"R SERIES" TRANSMISSION
RECEIVER & CAP



N400P

TRANSMISSION NOZZLE & PLUG PIN
LATCHING



N400RP

"R SERIES" TRANSMISSION NOZZLE
WITH PLUG, BALL LATCH, 3/4"



STANDARD

OPERATING PRESSURE

34.5 BAR

500 PSI

BURST PRESSURE

103.4 BAR

1500 PSI

FLOW AREA

.1136 SQ "

2.88544 mm

NOZZLE THREAD

1/2" MNPT

12.7 mm

RECEIVER THREAD

1/2" MNPT

12.7 mm

R SERIES

OPERATING PRESSURE

34.5 BAR

500 PSI

BURST PRESSURE

103.4 BAR

1500 PSI

FLOW AREA

.229 SQ "

5.8166 mm

NOZZLE THREAD

3/4" FNPT

19.05 mm

RECEIVER THREAD

OD 1-5/16" 12 TPI ID 1-1/16"

33.33mm OD, 26.98mm ID

*JIC bases on these receivers have extended JIC threads that can be fitted into a bulkhead; a female JIC hose can then be attached on the other side of the bulkhead. # R Series used for remote bulkhead mounting for common fluids. The receiver's dual threads are designed to allow bulk-head mounting using the male thread and connection of a hose to a leak-free female ORB thread. Note: R series couplers DO NOT connect with Standard couplers.

Only Trust your "FLUID EQUIPMENT SPECIALISTS"

WWW.SILVERIENG.COM | SALES@SILVERIENG.COM | 1300 716 413 | WHATSAPP +61 458 047 075